



Product Information

CR DEGREASER B

USAGE / DESCRIPTION

Cr Degreaser B is a blend of **tank cleaning additive** for cargo tank cleaning for the removal of heavy grease and oil sludge deposits from all surfaces. It is a universal cleaner that may be used with complete safety to the equipment and user. Yet, it easily penetrates thickened deposits of crude oil, hardened lube oil additive, vegetable oil, animal fats, tung oil, later fatty acid synthetic, coal and soot. Cramoil Cr Degreaser B is also commonly used as a hazardous solvent remover and for upgrading of "black cargo" crude or fuel oil tanks for gasoline or gas oil loading.

COMPARABLE MARKET PRODUCTS

CARECLEAN ECO CLEAN

CHEMLAB HAZARDOUS SOLVENT REMOVAL

TYPICAL SPECIFICATIONS

Specific Gravity at 20°C	:	0.95
Flash Point	:	Above 85°C
Appearance	:	Colour (saybolt) +20
Aromatic % Vol	:	75
Distillation Range (°C)	:	IBP min 180 DP max 265



Product Information

DIRECTIONS FOR USE & DOSAGE INSTRUCTION

Spraying Method

Never use this product neat. In areas of stains and hardened deposit **CR Degreaser B** may be diluted in the ratio of 1.5%. **CR Degreaser B** with 95% water and applied directly using a high pressure sprayer. It is recommended that the entire stain surface be wet with **Cr Degreaser B** and allowed to sit for 10 - 15 minutes before washing off with water. This procedure may be carried out at ambient temperature.

Circulation Method

Cr Degreaser B may be diluted in water to make a degreaser-water solution with 0.1% concentration of degreaser and circulated through the tank using a deep well pump. It is recommended that each wash cycle be for approximately 5 hours and at a temperature of 40°C – 45°C. *For more effective cleaning, the temperature may be raised to 65°C to 85°C. The cleaning solution often retains sufficient cleaning power after an initial wash that it may be recycled back to the tank for additional cleaning or cycled through other tanks. Water may then be used for a final wash to remove any residue.

***CAUTION:** Standard practices require that the cleaning temperature be 10°C below the boiling point of the lightest component of the cargo. This is to prevent vapour emission of the cargo during the cleaning process.

Immersion

Small parts/components may be cleaned by soaking them in a bath of **Cr Degreaser B** at a dosage of 3-8% degreaser-to-water solution.



Product Information

BENEFITS / ADVANTAGES

- 1) The introduction of a new type of break through surfactants enable highly concentrated solution of complexing agent, synthetic pyridine and surfactant to blend without any separation and enable a consistent concentration of **CR Degreaser B** to be applied during tank cleaning.
- 2) Due to the highly concentrated nature of the solution, a smaller amount will be required and used as compared to other standard degreaser. This result in considerable cost saving and a reduction in the ship's space required for the storages of cleaning chemical.
- 3) This **IMO approved product** is environment friendly, non flammable, highly effective and biodegradable.
- 4) Due to the additional of antifoam agent, **CR Degreaser B** will not produce any excessive foam which might create a problem to the ship's crew.

CARGO LIST

Cr Degreaser B is effective for the removal of the various cargo residues:

- All **mineral oils**, including but not limited to alpha olefins, camphor oil, carbolic oil, cashew nutshell oil, castor oil, crude palm oil, coconut oil fatty acid, corn oil, cottonseed oil, cottonseed oil stearine, latex, CTLA Polymer (Exxon), fish oil, tung oil, palm oil, peanut oil, sunflower oil.
- All **fats** including but not limited to fatty acids, fatty alcohols and animal fats, fatty acid synthetic.
- **Lubricant additives** from Exxon, Lubrizol Corporation, Shell and Chevron.
- **Petroleum products and petrochemicals** including but not limited to lubricants, diesel, jet fuel, fuel oil and dirty/sops oil tank, aromatic hydrocarbons, aliphatic and chlorinated hydrocarbons, butyl methacrylate monomer and other odouress product, phenol and wax and grease white, greaser pleshing, etc.
- **Coal and soot.**



Product Information

APPLICATIONS

Cr Degreaser B can be used on iron and steel surfaces. It can be used when diluted on a ratio of 1 part product to 10 parts water on epoxy and phenolics surface, but if it is used undiluted it must not stand for more than 3 hours.

HANDLING & PRECAUTIONS

This is a strong solution and protective clothing and goggles must be used when dispensing the product. Should the solution come into contact flush with generous amount of water, rinse with standard eyewash and get medical attention.