



Product Information

CR ENVIROCLEAN

USAGE / DESCRIPTION

Cr Enviroclean is a low toxicity **tank cleaning additive** that rapidly emulsifies natural oil and fats. It is also used for general degreasing on board the vessel.

TYPICAL SPECIFICATIONS

Specific Gravity at 20 ⁰ C	:	0.8965
Flash Point	:	78°C
Appearance	:	Yellowish
Distillation Range	:	185°C to 260°C
Storage	:	Three years under good storage condition

DIRECTIONS FOR USE & USAGE INSTRUCTION

Spraying Method

For cleaning on surface with heavy contaminants, it will be more effective to spray on the area with a high pressure sprayer. Wet the entire surface with neat **Cr Enviroclean** and allow 10 ~ 15 minutes for the solution to take effect before washing off the entire area with water at ambient temperature.



Product Information

Circulation Method


5% of **Cr Enviroclean** can be circulated by using the deep well pump through tank washing machine for approximately 5 hours at a temperature of between 40 ~ 50°C. The solution can be transferred to another tank for washing. The treated tank had to be cleaned thoroughly with water.

Rock & Roll Method

A solution of 5% **Cr Enviroclean** may be filled into the tank to be cleaned. By using the "Rock & Roll" motion of the ship movement when travelling, the tank may be cleaned in between voyage.

BENEFITS / ADVANTAGES

- * Fully Biodegradable.
- * Quickly emulsifies oil and mixable with water.
- * Low toxicity.



Product Information

1) **Cr Enviroclean** is extremely suitable for cleaning cargo tank which carry animal, mineral, vegetable, fish and oils.

2) Hydrocarbon Removal

For the removal of hydrocarbons and chloride. Also used widely in the cleaning of ship's bulkhead, sensitive electronic equipment and engine components.

3) General Cleaning

Cr Enviroclean can be used for general cleaning and degreasing.

HANDLING & PRECAUTIONS

Irritates the skin. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.